JET-LUBE® NO. 33



AUTOMOTIVE & INDUSTRIAL SILICONE GREASE

DESCRIPTION

JET-LUBE® NO. 33 is specifically formulated to meet the automotive specifications for aftermarket rebuilders of water pumps, alternators, ignition systems, and all low-friction bearing applications. JET-LUBE NO. 33 is well suited for rubber parts, "O" ring materials, gaskets, and low-friction plastic bearings. Its low volatility and low temperature properties allow the product consistency to remain constant over a wide temperature range. JET-LUBE NO. 33 is especially effective in bearing applications where start up in extreme low temperatures is necessary.

- Resistant to moisture and corrosive environments
- Nontoxic/Safe
- · Wide temperature range
- Chemical resistant
- · Highly resistant to oxidation and shear breakdown
- Compatible with many plastics
- NLGI Grade 2
- Chemical resistant
- Conforms to CID A-A-59173, Type 2 (formerly MIL-G-46886B)
- Conforms to former MIL Spec G-4343 for pneumatic systems, now SAE-AMS-G-4343

Additional uses for **JET-LUBE NO. 33** include:

- Freezer cart casters
- Utility disconnect switches and contacts
- · Windshield wiper motors and gears
- Spiral freezer bearings
- Freezer door hinges

PRODUCT CHARACTERISTICS

Thickener	Lithium
Fluid Type	Silicone
Color/Appearance	Light Pink Dropping
Point (ASTM D-566)	370°F (215°C)
Specific Gravity	1.0
Density (lb/gal), Typical	8.3
Flash Point (ASTM D-92), Typical	560°F (293°C)
Autoignition Point (Calculated)	>600°F (316°C) NLGI
Grade, Standard	2
Penetration	260 - 300
Copper Strip Corrosion	1A
(ASTM D-4048)	
Oil Separation, Wt. %	<1.0%

(24 hrs. @ 100°C) (ASTM D-6184)

Service Rating $-70^{\circ}\text{F} (-57^{\circ}\text{C}) \text{ to}$ $400^{\circ}\text{F} (204^{\circ}\text{C})$

PACKAGING

Code No.	Container Size	Container
73860	5 oz.	Tube
73850	14 oz.	Cartridge
73816	35 lb.	Pail
73824	120 lb.	Drum
73829	400 lb.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

0311

AUTHORISED DISTRIBUTOR

JET SEALANTS & LUBRICANTS

+91-22-24130003 info@jetsealants.in www.jetsealants.in