

JET-LUBE 5000™



INDUSTRIAL
INDUSTRIAL
INDUSTRIAL
INDUSTRIAL
INDUSTRIAL

WATER BASED CLEANER AND DEGREASER

DESCRIPTION

JET-LUBE 5000™ is a water-based cleaner/degreaser that uniquely combines nonhazardous cleaning agents with newly-developed emulsifying technology to provide a product that can effectively remove carbon, grease, oil, and other organic deposits while being both environmentally safe and ozone friendly. **JET-LUBE 5000** is tomorrow's answer to today's cleaning problems - totally effective yet safe for our environment and atmosphere. Use full strength for maximum results in shortest time.

Biodegradable	Noncaustic	Noncombustible
Noncorrosive	Nonflammable	Nonfuming
Nontoxic	pH Balanced	Water Soluble
NSF Registered		

JET-LUBE 5000 contains no 1:1:1 Trichloroethane, Fluorocarbons or SARA Title III, Section 313, Part 372-listed ingredients and contains no acids, alkalies, chlorides, ethylene glycol ethers, phosphates, or TTO's (Total Toxic Organic Compounds). EPA 624 and 625 test results are available upon request.

JET-LUBE 5000 is the safest and most effective cleaner/degreaser available and can be used for heavy duty parts degreasing, pressure washing, steam cleaning, ultrasound cleaning, or simply by brushing or spraying and then rinsing with water or wiping clean. **JET-LUBE 5000** is safe on all metal parts and most plastics.

APPLICATIONS

Automotive	Food Processing	Metal Fabrication
Aviation	Industrial	Residential
Electronics	Marine	Utilities

DILUTION RATIOS

JET-LUBE 5000 may be diluted with ordinary tap water or salt water (with reduced affect). Dilution ratios will vary greatly depending on the amount of buildup, temperature and speed required to complete the job. Suggested dilution ratios of water to **JET-LUBE 5000**:

DILUTE J-L 5000 to water	EQUIPMENT	CLEANING
1:4	Dip Tanks	Tools, Parts, Food Process Equipment, Presses, Aviation
1:3 - 5	Parts Washer	Engines, Exhaust Hoods, Fork Lifts, Graffiti, Marine
1:20+	Pressure Washer	Cleaning Parts, Floors and General Purpose
1:20+	Steam Cleaner	Engines, Parts, Etc.
1:10+	Ultrasound	For Cleaning Electrical Parts Etc.
1:25+	Trigger Sprayers, Pumps	General Purpose Cleaning and Facility Maintenance

RINSE AND WIPE DRY - TEST FOR COLOR FASTNESS

PRODUCT CHARACTERISTICS

Specific Gravity	1.0
pH	7-8
Viscosity (Cps)	4.5
Flash Point (PMCC Closed Cup) (ASTM D93)	None to 212°F
Auto Ignition Point	None to 500°F
Vapor Pressure @ 20°C	Composite <.04
Evaporation Rate (Butyl Acetate = 1)	>1
Vapor Density (Air = 1)	>1
Boiling Point	212°F (100°C)
Freezing Point	28°F
Volatile Organic Compounds (VOC) SCAQMD Rules 1171, 1122	None

- NSF (A1, B2 & C1) Reg. (#048229) for Federally Inspected Facilities
- Meets or exceeds Boeing D6-17487, Rev. J
- Meets or exceeds Douglas CSD #1, Reissued 3/24/89
- Meets or exceeds AMS 1526B (Aircraft Exteriors)
- Meets or exceeds EPA 624 and 625 requirements

PACKAGING

Code No.	Container Size	Container
71043	16 oz.	Spray Bottle
71033	1 gal.	Jug
71035	5 gal.	Jug
71029	50 gal.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

AUTHORISED DISTRIBUTOR
JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in