

CLEAN-UP II™ Aerosol



ORGANIC SOLVENT CLEANER & DEGREASER

DESCRIPTION

CLEAN-UP II™ is a specially formulated low VOC blend of organic solvents designed to quickly dissolve and rinse away dirt, grease, grime, oil, tar and wax while being both environmentally responsible and ozone friendly. The product contains no chlorinated or fluorinated solvents, no hazardous air pollutants and evaporates residue-free quickly. To evaporate quickly, however, **CLEAN-UP II** is flammable. This product is California compliant and acceptable for use in CARB/OTC States.

CLEAN-UP II starts working immediately on contact, breaking down and dissolving even stubborn contaminants without the use of fluorinated, chlorinated or SARA listed ingredients. **CLEAN-UP II** slowly evaporates while cleaning and leaves a residue-free surface. Safe on all metals and some plastics. Not recommended for sensitive plastics or certain painted surfaces. For sensitive materials, test on an inconspicuous small area first to determine acceptability. For electrical services the system must be off and time given to evaporate before re-energizing the system to avoid flash or fire.

- Replaces 1:1:1 Trichloroethane
- Low Odor
- Residue Free
- Safe on all Metals and most plastics
- Ozone Friendly
- Environmentally Responsible
- Convenient aerosol package
- Exempt from California VOC reporting

APPLICATIONS

CLEAN-UP PLUS is an ideal, environmentally responsible, ozone friendly product for a wide range of automotive, industrial, and marine cleaning applications such as:

Engine Components	Bearings	Electrical Motors
Appliances	Machine Parts	Cables Alternators
Tools	Gears	Metal Surfaces
Chains	Injectors Cranes	Forklifts Rotors
Drums	Winches	Wire Rope

PRODUCT CHARACTERISTICS

Solvent Type	Mixture of Acetone and Heptane isomers
Specific Gravity	0.789
Odor	light ketone, mild
Density (lb/gal)	6.58
Flash Point	< 0°F (-18°C) VOC Content 21.3 g/liter VOC Percent 2.7
VOC Category	Gen. Purpose Degreaser
VOC	70.2 g/L
Kauri Butanol Value (KB)	112
Propellant type	Carbon dioxide
Dielectric Strength & Breakdown Voltage (ASTM D-877)	6.3 KV AC
Flammability	Extremely flammable
Aerosol Flammability Level	III
California Compliant	YES

PACKAGING

Code No.	Container Size	Container
61442	14 oz.	Aerosol
61435	5 gal.	Pail
61429	50 gal.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

1211

AUTHORISED DISTRIBUTOR
JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in