

EP BEARING GREASE™



Industrial-grade, extreme-pressure, multipurpose grease

DESCRIPTION

EP BEARING GREASE™ is an all-purpose lithium grease containing naturally-occurring extreme-pressure and boundary lubricants. The additive package enhances the shear stability, lubrication properties and high temperature characteristics of lithium-based grease, making EP BEARING GREASE a versatile, cost-efficient, multipurpose grease. The extreme pressure additive has the added benefit of reducing acidity created by oxidation of the base fluid and organic additives in high-temperature environments. The result is a stable, high-temperature grease that will outperform most lithium-based greases on the market today.

EP BEARING GREASE is water resistant, highly tenacious, and has excellent resistance to the effects of salt spray, heat, water, oxidation, high loads and other adverse conditions common to industrial usage. This product will lower maintenance costs and simplify inventory while providing excellent all-around performance.

- Operating range from -0°F (-18°C) to 325°F (163°C)
- Superior rust and corrosion protection for maximum service life under harsh conditions
- Dropping point 390°F (199°C)
- Natural additives for resistance to extreme pressure
- Lithium 12-hydroxystearate base
- Color—Purple
- Highly adhesive to metal
- Industrial Grade

APPLICATIONS

Specially formulated for use on roller bearings, anti-friction bearings, journals, and is particularly useful where a single, multipurpose product is desirable. EP BEARING GREASE has a multitude of applications in industrial, automotive, mining, construction or anywhere an exceptionally high-quality, multipurpose lubricant is required.

PRODUCT CHARACTERISTICS

Thickener	Lithium
Fluid Type	Lubricating Oil
Color	Purple
Dropping Point (ASTM D-566)	390°F (199°C)
Specific Gravity	0.95
Density (lb/gal)	8.0
Additive Type	EP/AW, R&O
Flash Point (ASTM D-92)	>430°F (221°C)
Autoignition Point (CALCULATED)	>500°F (260°C)
NLGI Grade	2
Penetration @77°F (ASTM D-217)	265-295
Copper Strip Corrosion (ASTM D-4048)	1B
Shell 4-Ball (ASTM D-2596)	
Weld Point, kgf	315
Load Wear Index	38
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942)	
PSI Drop, 100 hours	<5.0
Base Oil Viscosity (ASTM D-445)	
cSt @ 40°C	200 typical

PACKAGING

Code No.	Container Size	Container
30350	14 oz.	Cartridge
30316	35 lb.	Pail
30324	120 lb.	Drum
30329	400 lb.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

AUTHORISED DISTRIBUTOR

JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in

INDUSTRIAL INDUSTRIAL INDUSTRIAL INDUSTRIAL INDUSTRIAL