

GEAR GUARD™

OPEN GEAR LUBRICANT PASTE



INDUSTRIAL
INDUSTRIAL
INDUSTRIAL
INDUSTRIAL

DESCRIPTION

JET-LUBE's GEAR GUARD™ is a paste-like, viscous lubricant for reducing friction and wear. It is a heavy-duty compound, specially prepared to penetrate pores of metal, with exceptional "stay-put" characteristics. It provides maximum lubrication and shock-load protection, reduces gear noise, lubricates, prevents scoring and welding of gear teeth. **GEAR GUARD** penetrates strands of wire rope and cable to replenish the original lubricant in the core itself.

GEAR GUARD assures a smooth, long-lasting, economical, and effective coating. Its black color guides proper coverage, allowing easy touch up. It does not have to be heated. **GEAR GUARD** resists heat and pressure, will not wash or wear off because of weather, and will not break down after repeated workings. It contains rust-preventing ingredients and is moisture resistant, actually displacing water.

CHARACTERISTICS

Quality ingredients for optimum lubrication and resistance. The ingredient, molybdenum disulfide (MoS₂) is twice as "slippery" as graphite, has an affinity for ferrous metals, and bonds itself to steel working surfaces. MoS₂ protects working surfaces from frictional wear, reduces fret-corrosion, and will sustain lubrication when the film of a conventional lubricant has been displaced for any reason.

GEAR GUARD also contains a special grease additive, **JET-LUBE's CZ-EX®**, an extreme pressure additive. **CZ-EX** increases performance because it maintains the proper dispersion and suspension of solid ingredients. It flows evenly and will not drip, assuring that the surface receives maximum protection.

APPLICATIONS

JET-LUBE's GEAR GUARD is used on open gears, chains, cables, or wire ropes. It is ideal for fifth wheels of tractors and trucks, leaf springs, drive chains, screw threads, flexible couplings, and die-set leader pins. It can be used on racks and pinions, edges, roller gears, agitator drive and winches.

Application by aerosol spray lets it dry quickly, preventing dust contamination and dripping. "Thin-film" lubrication reduces costly power loss through "in-lubricant" friction. This method substantially reduces application time and eliminates messy handling, brushes, paddles, and waste. Contains nonfluorocarbon propellants.

PRODUCT CHARACTERISTICS

Fluid Type	Petroleum Oil
Specific Gravity	1.10
Density (lbs./gal.)	9.15
Rust Test (ASTM D-665)	Pass
4-Ball EP Test	620
(ASTM-2783) WELD POINT, kfg	
Flash Point (ASTM D-92)	>430°F (221°C)
Color Appearance	Black, Sticky Semi-Fluid

SERVICE RATING

-25°F (-32°C) to 350°F (175°C)

Color: Black

PACKAGING

Code No.	Container Size	Container
17941	12 oz.	Aerosol
See Aerosol MSDS/Bulletin		
17909	9 lb.	Pail
17916	35 lb.	Pail

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

AUTHORISED DISTRIBUTOR
JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in