



JET-LUBE® JACKING SYSTEM GREASE™ ECF™

OSPAR Commission - HOCNF

Classification - "Yellow" Rating for Norway

- "E" for the United Kingdom & The Netherlands

DESCRIPTION

JET-LUBE® JACKING SYSTEM GREASE™ ECF™ is safe to use in offshore applications since it is metal free and is formulated to conform to the strict North Sea Environmental Guidelines. It utilizes a water-resistant, complex thickener that is enhanced to improve adhesion and provide greater protection against water washoff, wear, and corrosion. **JET-LUBE JACKING SYSTEM GREASE ECF** contains specially selected solid natural boundary lubricants to provide outstanding galling resistance and lubrication properties. The solid boundary and organic EP additives synergistically combine to produce a superior lubricating film with high-load and low-wear characteristics.

APPLICATIONS

JET-LUBE JACKING SYSTEM GREASE ECF is designed to lubricate a wide array of heavily loaded gear applications. It can also be used on slides, jacking systems, cantilever type rigs and assemblies, nuts, bolts, and a wide range of other applications - making **JET-LUBE JACKING SYSTEM GREASE ECF** a nearly universal product.

- Excellent Environmental Properties
- High Load Resistant
- Water Resistant
- Corrosion Resistant
- Nonmetallic
- Safe for Offshore Personnel
- Biodegradable, non-bioaccumulative
- Outstanding Film Strength
- Easy to Apply

This product is formulated to contain no detectable, leachable, volatile organics by EPA Test Method 1311-TCLP number SW846 8260B as determined by independent, 3rd party testing. Testing results are available upon request.

PRODUCT CHARACTERISTICS

Appearance	Beige Tacky Grease
Fluid Type	Synthetic & Vegetable
Thickener	Complex
Specific Gravity	1.26
Density (lbs/gal)	10.55
Cone Penetration	300 - 330
	@ 77°F (ASTM D-217)
Dropping Point	>200°F (93°C), typical
	(ASTM D-2265)
4-Ball (ASTM D-2596)	≥ 800
	(7845) Weld Point, kgf (N)
Gas Evolution	None,
typical Oil Separation	<1%, typical
Water Leaching	
	2 hrs. @ 150°F
Service Rating	<4°F (-20°C) to
	300°F (149°C)
EPA 1311-TCLP	Non-detected

PACKAGING

Code No.	Container Size	Container
25815	44 lb. (20 kg.)	Pail
25816	5 gal.	Pail
25824	15 gal.	Drum
25829	55 gal.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

1011

AUTHORISED DISTRIBUTOR

JET SEALANTS & LUBRICANTS

+91-22-24130003

info@jetsealants.in

www.jetsealants.in