

NIKAL[®]

HIGH TEMPERATURE ANTI-SEIZE AND GASKET COMPOUND



INDUSTRIAL
INDUSTRIAL
INDUSTRIAL
INDUSTRIAL

DESCRIPTION

NIKAL[®] is a premium quality anti-seize and gasket compound for use in extreme temperatures and hostile environments. The carrier of this remarkable compound volatilizes upon exposure to high temperatures and deposits a nickel metallic plating on threaded connections, preventing metal-to-metal contact and guarding against seizing and galling.

NIKAL contains pure nickel flake and a nearly inert dispersing solid in a high quality aluminum complex base grease that provides unsurpassed protection from rust by water penetration or water washoff.

NIKAL does not contain copper, lead, graphite, molybdenum MOSL, chlorides or other halogens, phosphorus, or silicones. It may be safely used with ammonia, acetylene and vinyl monomers, which are unstable in the presence of copper. **NIKAL** contains no graphite, which is an additional benefit on stainless steel applications when temperatures exceed 550°F, as graphite can carburize the steel causing the steel to become much more susceptible to intergranular corrosion. The solids package in **NIKAL** produces a matrix of particles that settle in successive layers or "sandwich." This allows the solids to serve as a lubricant, cushion and seal. This layering does not allow the welding under compaction that leads to seizure and galling.

- Contains no lead, copper or graphite
- Prevents seizure up to 2600°F (1427°C)
- Protects against rust and corrosion
- Chemically inert
- Acid resistant
- Strong resistance to water washoff
- Brushable to 0°F (-18°F)
- Will not run, drip or settle out.
- Color - Silver

APPLICATIONS

Used extensively in refineries, chemical plants, petrochemical plants, power generation facilities and other harsh environments on items such as:

Burner Tips
Heat Exchangers
Furnace Hinges
Pipe Fittings

Reactor Bolts
Manifolds
Manhole Studs

| | |
|---|---|
| CONFORMS TO: Military Specification MIL-PRF-907E | SERVICE RATING: -65°F (-54°C) to 2600°F (1427°C) |
|---|---|

NOT FOR USE ON OXYGEN LINES.

PRODUCT CHARACTERISTICS

| | |
|--|-------------------|
| Thickener | Aluminum Complex |
| Fluid Type | Petroleum |
| Color/Appearance | Silver/Grey Paste |
| Dropping Point (ASTM D-566) | 450°F (232°C) |
| Specific Gravity | 1.10 |
| Density (lb/gal) | 9.20 |
| Oil Separation | <5.0 |
| Wtr. % Loss @ 212°F (100°C) | |
| Flash Point (ASTM D-92) | >430°F (221°C) |
| K-Factor | .15 |
| High Chrome Alloys @ 60,000 PSI | Contact Stress |
| NLGI Grade | 1½ |
| Penetration @77°F (ASTM D-217) | 300 - 315 |
| Copper Strip Corrosion (ASTM D-4048) | 1A |
| Shell 4-Ball (ASTM D-2596) | |
| Weld Point, kgf | 200 |
| Load Wear Index | Not Applicable |
| Salt Fog Resistance (ASTM B-117) | +200 |
| 20% NaCl @ 100°F, Hrs. Free of Corrosion | |

PACKAGING

| Code No. | Container Size | Container |
|----------|----------------|---------------|
| 13655 | ¼ lb. | Brush Top can |
| 13602 | ½ lb. | Brush Top can |
| 13604 | 1 lb. | Brush Top can |
| 13607 | 2 lb. | Plug Top can |
| 13623 | 8 lb. | Pail |
| 13613 | 20 lb. | Pail |
| 13615 | 40 lb. | Pail |

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

AUTHORISED DISTRIBUTOR

JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in