

# PETRO-TAPE™

## POLYTETRAFLUOROETHYLENE HEAVY-DUTY THREAD SEAL TAPE



### DESCRIPTION

JET-LUBE® PETRO-TAPE™ is made of pure, virgin polytetrafluoroethylene. It withstands low temperatures to -400°F (-240°C), high temperatures to 500°F (260°C). This rugged, inert and highly resistant tape is impervious to steam, salt water, air, fuels, refrigerants, acids and alkalies (including sulfuric, hydrochloric, nitric, sodium hydroxide and chromic), solvents (including kerosene, aircraft oils, gasoline, carbon tet. and cleaning fluids) and gases (including liquid and gaseous oxygen, hydrogen, ammonia, freon, chlorine, propane, butane and nitrogen). Its characteristics make it far superior to other PTFE tapes for heavy-duty use.

PETRO-TAPE is easy, quick and clean to use. Just wrap one turn of tape around the pipe, stretch it to break and join. There is no need to wait for it to set, and the joint can be disassembled now or at any future time. PETRO-TAPE cannot drip or run, and it never dries out. It is ready for instant use, now or years from now, because it keeps its protective qualities indefinitely.

PETRO-TAPE is packaged to protect it from dirt and damage. It is wound on a durable, corrosion resistant plastic spool, which is locked into a matching shell. The strength of this packaging protects the tape from tools in the toolbox or dust, grease, moisture and grime in the environment or pocket. It also reduces the chance of accidental unwinding or crumpling.

Use PETRO-TAPE on all threaded pipe connections, valve stems, hydraulic pressure lines and many other fittings. It is adaptable to all threaded materials, including galvanized iron, stainless steel, synthetic rubber, aluminum, plastics, copper, brass, black iron and more.

- Use where strength is needed
- Thick
- Resistant
- Inert properties
- Conforms to CID A-A-58092 (formerly MIL T-27730A)
- Service Rating: -400°F (-240°C) to 500°F (260°C)
- Minimum 3 mils. (0.003") Thickness

### PACKAGING

Code No.	Container Size	Container
30774	1/2"	520" Spool

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

**AUTHORISED DISTRIBUTOR**  
**JET SEALANTS & LUBRICANTS**

**+91-22-24130003**  
**info@jetsealants.in**  
**www.jetsealants.in**