

RUST-GUARD™

CORROSION INHIBITOR



DESCRIPTION

RUST-GUARD™ is a water displacing specialized formula which dries to a uniform, thin waxy film to effectively seal out moisture and corrosion. **RUST-GUARD** provides long-term protection on all metal and alloy surfaces, even under harsh environmental conditions such as water, high humidity or salt spray. Bulk formula typically provides six months outdoor and one year indoor protection against rust and corrosion.

RUST-GUARD may be used both indoors or outdoors as a protective coating on raw materials, machined parts, tools, pipe, fittings, valves, etc., while they are being stored or in transit. **RUST-GUARD** will not crack or flake off and, since it is applied in aerosol or liquid form, it penetrates fully into even the smallest crevices to displace moisture and prevent rust and corrosion. **RUST-GUARD** is green in color to facilitate visual check of product application and is easily and safely removed by use of a safety solvent such as **JET-LUBE® CLEAN-UP™**.

- Nontoxic
- Economical to use
- Penetrates deeply, displacing moisture
- Prevents rust and corrosion
- Indoor/Outdoor formula
- Will not crack/peel off
- Easily removed
- Available in convenient aerosol package
- Visually identifiable blue-green color
- For tubing, casing, line pipe, and rotary shouldered connections. Removal prior to application of running compounds is not necessary
- Conforms to MIL-PRF-16173E Grades 1 and 2

APPLICATIONS

RUST-GUARD may be used to provide long-term protection from rust and corrosion for a variety of Industrial, Marine, Aviation, and Oilfield applications.

PRODUCT CHARACTERISTICS

Film Material	Calcium Soap/Wax
Fluid Type	Mineral Spirits
Color/Appearance	Blue-Green Fluid
Specific Gravity	0.85
Density (lbs/gal)	7.07
Flash Point (ASTM D-1310) T.O.C.	>100°F (38°C)
Melting Point (of finished film)	280°F (138°C)
Film Thickness, Mills (TYPICAL)	0.5
Copper Strip Corrosion (ASTM D-130)	1B Max
Salt Fog Resistance (ASTM B-117)	No Rust > 20 Days
Underwater Submersion	No Rust > 30 Days
Humidity Resistance	No Rust > 30 Days
VOC	193.4 g/L

COVERAGE INFORMATION

The coverage area provided by **RUST-GUARD** will vary with film thickness, surface finish and loss or spillage. Typical results may be expected:

- 0.25 mils can cover up to 3,600 sq. ft. per gallon
- 0.50 mils can cover up to 1,800 sq. ft. per gallon
- 1.00 mils can cover up to 900 sq. ft. per gallon

PACKAGING

Code No.	Container Size	Container
13241	11 oz.	Aerosol
See Aerosol MSDS/Bulletin		
13233	1 gal.	Can
13235	5 gal.	Pail
13229	50 gal.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

1211

AUTHORISED DISTRIBUTOR
JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in