

WHITE LITHIUM GREASE WITH PTFE



INDUSTRIAL
INDUSTRIAL
INDUSTRIAL
INDUSTRIAL
INDUSTRIAL

DESCRIPTION

WHITE LITHIUM GREASE with PTFE is a premium, all-purpose grease that provides superior performance and protection for metal and moving parts under any use. **WHITE LITHIUM GREASE** with PTFE penetrates and forms a long-lasting protective film to withstand heavy loads and high speeds, prevents rust and corrosion, eliminates squeaks and squeals and will not run or wash away.

WHITE LITHIUM GREASE with PTFE is excellent for all metal-to-metal lubrication and is the preferred lubricant for use in the plant, shop, home, auto and boat.

- Available in convenient aerosol package
- NSF Reg. #137549
- Clean, White Color
- Multi-Purpose
- Water Resistant
- Prevent Rust and Corrosion
- Very Adhesive
- Resists Heat and Oxidation

APPLICATIONS

GENERAL PURPOSE LUBRICANT

INDUSTRIAL - machinery, tools, overhead garage door channels, fan motors, slides, gears...

MARINE - cables, couplings, gears, hitches, winches...

AUTOMOTIVE - hinges, electric antennas, latches, springs, coils...

RESIDENTIAL - implements, door channels, slides, locks...

FOOD SERVICE - all areas where food contact cannot occur.

SERVICE RATING:
0°F (-18°C) to 370°F (190°C)

- NSF (H-2) Registered, Meets 1998 USDA (H-2) Guidelines For Use In Federally Inspected Meat and Poultry Plants in Noncontact Areas
- Authorized for use by Agriculture Canada

PRODUCT CHARACTERISTICS

Thickener	Lith. 12-hydroxy
Fluid Type	Petroleum Oil
Color/Appearance	White
Dropping Point (ASTM D-566)	390°F (199°C)
Specific Gravity	0.95
Density (lbs/gal)	7.80
Additive Type	Organic E/P, A/W, R&O
Flash Point (ASTM D-92)	
Bulk	>430°F (221°C)
Aerosol	104°F (40°C)
Autoignition Point (calculated)	>500°F (260°C)
NLGI Grade	2
Penetration @ 77°F (ASTM D-217)	265 - 295
Copper Strip Corrosion (ASTM D-4048)	1A
Shell 4-Ball (ASTM D-2596)	
Weld Point, kgf	200
Load Wear Index	25
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942)	
PSI Drop, 100 hrs.	<5
Base Oil Viscosity (ASTM D-445)	
cSt @ 40°C	100 - 160

PACKAGING

Code No.	Container Size	Container
50350	14 oz.	Cartridge
50305	1 lb.	Can
50341	13 oz.	Aerosol
	See Aerosol MSDS/ Bulletin	
50316	35 lb.	Pail
50324	120 lb.	Drum
50329	400 lb.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

AUTHORISED DISTRIBUTOR
JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in