

JET-LUBE® WIRE LINE LUBRICANT ECF™

Ospar Commission-HOCNF
(Harmonized Offshore Chemical Notification Format)
CLASSIFICATION: "Yellow" rating for Norway
CLASSIFICATION: "E" for The United Kingdom
& The Netherlands



DESCRIPTION

JET-LUBE® WIRE LINE LUBRICANT ECF™ is a unique product for wire line applications where a grease-type lubricant is required. Specially formulated for slick line, electric line, and braided line, this new-generation formula is certified to meet the "Yellow" environmental category for Norway, conforms to the Norwegian requirements for biodegradability, and passes the biotoxicity test. **WIRE LINE LUBRICANT ECF** is H₂S inhibited and has unique capabilities as a preservative against rust and corrosion. It also offers excellent protection against extended exposure to the elements and UV rays.

WIRE LINE LUBRICANT ECF can be applied by hand or through a pneumatic lubrication system. This easy-flow formula will stick to the wire line and penetrate the wire core for added protection and wire line life.

- Easy to apply
- Nonconductive
- Outstanding rust prevention
- Norwegian "Yellow" environmentally safe
- Wide temperature service
- Extremely water resistant
- Contains no VOC's

This product is formulated to contain no detectable, leachable, volatile organics by EPA Test Method 1311-TCLP number SW846 8260B as determined by independent, 3rd party testing. Testing results are available upon request.

APPLICATIONS

WIRE LINE LUBRICANT ECF is ideally suited for the following applications:

- Corrosive Environments
- Braided Line
- Temperature Surveys
- Gas Lift Services
- Deep Water Wire Line
- Slick Line
- Electric Line
- Perforating
- Fishing Operations

PRODUCT CHARACTERISTICS

Color	Lt. Beige
Appearance	Buttery grease
Cone Penetration (ASTM D-217)	
Unworked	295 - 340
60 Strokes	310 - 330
10,000 Strokes	+10%
Oil Separation, 100°C 24 hrs.	5% max.
Load Wear Index	31 typ.
Salt Fog Corrosion Resistance	>1000 hrs.
20% NaCl, 100°F	
Low Temperature Flexibility	Pass
Volatile Matter	<2%
Service Rating	-20°F to 500°F -29°C to 260°C
EPA 1311-TCLP	Non-detected

Note: Not for use with oxygen or strong oxidizers such as hydrogen peroxide or sulfuric acid.

PACKAGING

Code No.	Net Weight	Container
29316	35 lb.	Pail

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages

1011

AUTHORISED DISTRIBUTOR
JET SEALANTS & LUBRICANTS

+91-22-24130003
info@jetsealants.in
www.jetsealants.in